

CLAIMS

1. A method of using a system bus on a configurable system on a chip (CSoC), the CSoC including configurable system logic (CSL), the method comprising:

configuring a memory cell in the CSL using the system bus; and

reading the memory cell in the CSL using the system bus.

2. The method of Claim 1 wherein the system bus is controlled by a direct memory access (DMA) controller during the step of configuring.

3. The method of Claim 1 wherein the system bus is controlled by a central processing unit (CPU) during the steps of configuring and reading.

4. A method of initializing a configurable system on a chip (CSoC), the CSoC including configurable system logic (CSL), the method comprising:

selecting one of a plurality of clocks before configuring the CSL;

configuring the CSL; and

selecting one of the plurality of clocks after configuring the CSL.

5. A method of initializing a configurable system on a chip (CSoC), the CSoC including configurable system logic (CSL), the method comprising:

1 checking for one of a serial and a parallel output  
2 device external to the CSoC and coupled to a memory  
3 interface unit (MIU) in the CSoC;  
4 setting the MIU to an appropriate mode based on the  
5 output device;  
6 searching for a header in the output device;  
7 switching to another mode if the header is not found;  
8 and  
9 configuring the CSL if the header is found.

10  
11 6. The method of Claim 5, wherein if the header is not  
12 found in the other mode, then further including:  
13 checking whether the output device is accessible;  
14 powering down the CSoC if the output device is  
15 accessible; and  
16 repeating the steps in Claim 5 if the output device is  
17 not accessible.

18  
19 7. A programmable interconnect structure providing a  
20 signal to a logic block, the interconnect structure  
21 comprising:  
22 a plurality of interconnect lines divided into sets of  
23 interconnect lines;  
24 a plurality of first-tier multiplexers, each first-  
25 tier multiplexer having input terminals coupled to a set of  
26 interconnect lines and having an output terminal;  
27 a plurality of second-tier multiplexers, each second-  
28 tier having a first input terminal coupled to one output  
29 terminal of the first-tier multiplexers and a second input  
30 terminal coupled to a constant voltage source,

1 wherein the plurality of second-tier multiplexers  
2 selectively provide output signals from the first terminals  
3 or the second terminals to the logic block.

4  
5 8. A method of providing signals to a logic block, the  
6 method comprising:

7 selectively providing one of a plurality of  
8 interconnect signals and a constant logic signal to the  
9 logic block,

10 wherein during a configuration mode, the constant  
11 logic signal is provided to the logic block, and

12 wherein during a user mode, the plurality of  
13 interconnect signals are provided to the logic block.

14  
15 9. An input multiplexer to a logic block, the input  
16 multiplexer comprising:

17 a first multiplexer receiving a first plurality of  
18 input signals and a constant signal;

19 a second multiplexer receiving a second plurality of  
20 input signals and a mode signal;

21 a third multiplexer receiving output signals from the  
22 first and second multiplexers and providing an output  
23 signal on a logic block input line; and

24 a first transistor coupled to an internal logic block  
25 line, the first transistor controlled by the mode signal.

26  
27 10. A method of providing signals on an internal logic  
28 block line of a logic block, the method comprising:

29 providing a plurality of input signals to a plurality  
30 of selectors, wherein each selector further receives one of  
31 a constant logic value and a mode signal;


1 selectively providing one of the plurality of input  
2 signals, the constant logic value, and the mode signal on  
3 the internal logic block line, wherein the mode signal  
4 indicates whether the logic block is in a configuration  
5 mode or a user mode.  
6

7 11. The method of Claim 10, wherein during configuration,  
8 the plurality of input signals, the constant logic value,  
9 and the mode signal have the same value.  
10

11 12. The method of Claim 10, wherein during the user mode,  
12 the constant logic value and the mode signal have different  
13 values.  
14

15 13. The method of Claim 10, further including using the  
16 mode signal to transfer the constant logic value to the  
17 internal logic block line.

add 4  
add  
134



---

**COMBINED DECLARATION AND POWER OF ATTORNEY**

(ORIGINAL, DESIGN, NATIONAL STAGE OF PCT, SUPPLEMENTAL, DIVISIONAL,  
CONTINUATION, OR C-I-P)

---

As a below named inventor, I hereby declare that:

**TYPE OF DECLARATION**

This declaration is for an original application.

**INVENTORSHIP IDENTIFICATION**

My residence, post office address and citizenship are as stated below, next to my name. I believe that I am the original, first and sole inventor (*if only one name is listed below*) or an original, first and joint inventor (*if plural names are listed below*) of the subject matter that is claimed, and for which a patent is sought on the invention entitled:

**TITLE OF INVENTION**

**"Configuration In A Configurable System On A Chip"**

**SPECIFICATION IDENTIFICATION**

In re application of: Brian Fox and Andreas Papaliolios  
Serial No. 09/419,386  
Filed on: 10/15/1999

**ACKNOWLEDGMENT OF REVIEW OF PAPERS AND DUTY OF CANDOR**

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information, which is material to patentability as defined in 37, Code of Federal Regulations, §1.56, and which is material to the examination of this application, namely, information where there is a substantial likelihood that a reasonable Examiner would consider it important in deciding whether to allow the application to issue as a patent.

**POWER OF ATTORNEY**

I hereby appoint the following practitioners to prosecute this application and transact all business in the Patent and Trademark Office connected therewith.

Patrick T. Bever  
E. Eric Hoffman  
Jeanette S. Harms  
Edward S. Mao  
Julie A. Stephenson

Registration Number 33,834  
Registration Number 38,186  
Registration Number 35,537  
Registration Number 40,713  
Registration Number 41,330

SEND CORRESPONDENCE TO

DIRECT TELEPHONE CALLS TO:

Jeanette S. Harms, Esq.  
BEVER & HOFFMAN, LLP  
2099 Gateway Place, Suite 320  
San Jose, CA 95110-1017

(408) 451-5907

DECLARATION

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code, and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

SIGNATURE(S)

Brian Fox

Inventor's signature

Date 11/18/99

Residence Sunnyvale, CA

Post Office Address 1414 Mallard Way  
Sunnyvale, CA 94087

Country of Citizenship United States

Andreas Papaliolios

Inventor's signature

Date 24 Nov 99

Residence Sunnyvale, CA

Post Office Address 1338 Torrance Avenue  
Sunnyvale, CA 94089

Country of Citizenship United States